



Amplifier Bypass Harness

Fits Select Honda Models 2008-2017

FEATURES

- Vehicle-specific harness to bypass the factory amplifier
- Saves the installer unnecessary labor and wire
- 20 gauge wires
- Wire Length: 12"

Refer to the following pages for the vehicle specific instructions for wiring connections. Wiring connections vary per vehicle. Please note that there are (2) different wiring harnesses included, and the instructions for each harness will be listed.

If it's uncertain whether the vehicle contains a specific speaker or not, test the wires with a tone generator, or check to see if the factory wires are populated on the vehicle side. Alternatively, the wires can be tested for impedance with a multimeter.

APPLICATIONS

HONDA		CR-V	2010-2016	HR-V	2016-2017	Ridgeline	2009-2017
Accord	2008-2017	CR-Z	2011-2017	Insight	2010-2014	Pilot	2009-2016
Civic	2009-2015	Fit	2009-2017	Odyssey	2011-2017		

TABLE OF CONTENTS

Amplifier locations	2
Connections	3

TOOLS REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink
- Tape • Wire cutter • Zip ties

Visit AxxessInterfaces.com for more detailed information about the product and up-to-date vehicle specific applications.

Attention! Let the vehicle sit with the key out of the ignition for a few minutes before removing the factory radio. When testing the aftermarket equipment, ensure that all factory equipment is connected before cycling the key to ignition.

AMPLIFIER LOCATIONS

Vehicle

Amp Location

Accord	Center console, close to firewall
Civic	2-Door: Center Console; 4-Door: Below Driver's Seat
CR-V	Under gear selector in center console
CR-Z	In the Dashboard, behind Audio Unit, to the Left
Fit	N/A
HR-V	N/A
Insight	In the Passenger Compartment, behind the Glovebox
Odyssey	In the Passenger Compartment, behind the Glovebox
Ridgeline	In the Passenger Compartment, behind the Glovebox
Pilot	Passenger's Kick Panel area, up high in the dashboard

CONNECTIONS

18-Pin Harness:

Wire Color	Speaker
White	Front Left Woofer +
White/Black	Front Left Woofer -
Gray	Front Right Woofer +
Gray/Black	Front Right Woofer -
Yellow/Blue	Front Left Tweeter +
Yellow/Black	Front Left Tweeter -
Yellow/Red	Front Right Tweeter +
Yellow/Orange	Front Right Tweeter -
Green	Rear Left Speaker +
Green/Black	Rear Left Speaker -
Purple	Rear Right Speaker +
Purple/Black	Rear Right Speaker -
Brown/White	Center Channel Speaker+
Blue/Pink	Center Channel Speaker -
Green/White	Subwoofer +
White/Red	Subwoofer -

8-Pin Harness:

Wire Color	Speaker
Blue/Orange	Left Satellite Speaker +
Blue/Red	Left Satellite Speaker -
Blue/Yellow	Right Satellite Speaker +
Blue/Green	Right Satellite Speaker -
Green/Orange	Rear Left Tweeter +
Green/Red	Rear Left Tweeter -
Black/Yellow	Rear Right Tweeter +
Black/Green	Rear Right Tweeter -

Note: These speakers are not present in all applications. Test the wires with a multimeter to verify whether they are applicable or not.



AXABH-HN1

INSTALLATION INSTRUCTIONS



Having difficulties? We're here to help.



Contact our Tech Support line at:

386-257-1187



Or via email at:

techsupport@metra-autosound.com

Tech Support Hours (Eastern Standard Time)

Monday - Friday: 9:00 AM - 7:00 PM

Saturday: 10:00 AM - 5:00 PM

Sunday: 10:00 AM - 4:00 PM



**Metra recommends MECP
certified technicians**