

MULTI-MOUNT ACCESSORY CAMERA



CELEBRATING
75
YEARS

IMPROVED!



TE-2MPC MULTI-MOUNT ACCESSORY CAMERA



SALES 386-257-2956



PRODUCT OVERVIEW

See an unobstructed view while driving with a rear camera that can stay active while the vehicle is on, not just when it is in reverse*. This universal camera is ideal for keeping an eye on cargo, a trailer hitch, or reducing blind spots in the back of the vehicle while driving. iBEAM's TE-2MPC camera includes a 27ft extension harness and multiple mounts for installation behind the license plate, surface mounting, or flush mounting. This camera has a resolution of 640 TV lines (CVBS) or 1280 TV Lines (AHD), with a 1/3" CMOS sensor and a CVBS 150-degree viewing angle or AHD 152-degree viewing angle. It features an improved power circuit, is rated IP67 for water resistance, and has a durable metal housing.

Features:

- Multiple mounts included - behind plate mount, surface mount, and flush mount
- Improved power circuit
- Selectable parking line
- Mirror image option
- Can be viewed while driving, with a compatible monitor
- Water-resistant to protect from the elements
- IP rating: IP67
- Mounting: Front or rear
- 3-year warranty

Specs:

Image sensor: 1/3 inch CMOS
TV system: CVBS 640TV lines; AHD 1280TV lines
Effect pixels: 1280(H) x 720(V)
Pixel size: 3.75 Qmx 3.75 Qm
Min illumination: 0.1 Lux
Video out: 1MP, 720P@60fps
Sensitivity: 12448mV/Lux-s
Power supply: 9-16VDC
Lens spec: 6G+1IRF
Diagonal viewing angle: AHD 152°; CVBS 150°
Current consumption: $\leq 120\text{mA}$
Operating temperature: -20 to +70°C
Storage temperature: -30 to +85°C

Wire Lengths:

- Extension cable: 8.2M / 27'
- Camera cable: 1.5M / 5'

