

MULTI-MOUNT ACCESSORY CAMERA



CELEBRATING
75
YEARS

IMPROVED!



TE-2MPC

MULTI-MOUNT ACCESSORY CAMERA



SALES 386-257-2956



Wire Lengths:

- Extension cable: 8.2M / 27'
- Camera cable: 1.5M / 5'

PRODUCT OVERVIEW

Enjoy an unobstructed view while driving with a rear camera that stays active while the vehicle is on, not just when it is in reverse*. This universal camera is ideal for monitoring cargo, the trailer hitch, or reducing blind spots at the rear of the vehicle while driving. iBEAM's TE-2MPC camera includes a 27-foot extension harness and multiple mounts for installation behind the license plate, surface mounting, or flush mounting. This camera has a resolution of 640 TV lines (CVBS) or 1280 TV Lines (AHD), with a 1/3" CMOS sensor and a CVBS 140-degree viewing angle or AHD 145-degree viewing angle. It features an improved power circuit, is rated IP67 for water resistance, and has a durable metal housing.

Features:

- Multiple mounts included - behind plate mount, surface mount, and flush mount
- Improved power circuit
- Selectable parking line
- Mirror image option
- Can be viewed while driving, with a compatible monitor
- Water-resistant to protect from the elements
- IP rating: IP67
- Mounting: Front or rear
- 3-year warranty

Specs:

- Image sensor: 1/3 inch CMOS
- TV system: CVBS 640TV lines; AHD 1280TV lines
- Effect pixels: 1280(H) x 720(V)
- Pixel size: 3.75 Qmx 3.75 Qm
- Min illumination: 0.1 lux
- Video out: 1MP, 720P@60fps
- Sensitivity: 12448mV/lux·s
- Power supply: 9-16VDC
- Lens spec: 6G+IR
- Diagonal viewing angle: AHD 145°; CVBS 140°
- Current consumption: ≤120mA
- Operating temperature: -20 to +70°C
- Storage temperature: -30 to +85°C