SPEAKER KITS FITS SELECT TESLA MODELS







OS-TESLA8W 8" MIDWOOFER SPEAKER KIT

Features

- · Direct fit plugs
- Custom torsion basket fits directly into factory speaker location
- Lightweight, rigid composite paper and wood fiber cone design for a natural vocal reproduction
- · Carbon fiber dust cap enhances strength and durability
- Neodymium magnets deliver immense motor force while maintaining compact size and lightweight design
- Dynamic foam surround offers a wide frequency response and excellent excursion, ensuring clear and immersive sound

Includes:

• 2 direct-replacement speakers & vehicle-specific speaker harness

Specifications:

- 8" Woofer 1-Way Configuration
- Peak/RMS Power: 400W/200W
- · Sensitivity: 88dB
- Frequency Response: 55Hz 3kHz
- Impedance: 4 Ohm



OS-TESLA4M

4" MIDWOOFER SPEAKER KIT

Features:

- Direct fit plugs
- Custom torsion basket fits directly into factory speaker location
- Lightweight, rigid composite paper and wood fiber cone design for a natural vocal reproduction
- · Carbon fiber dust cap enhances strength and durability
- Neodymium magnets deliver immense motor force
- Dynamic foam surround offers a wide frequency response and excellent excursion, ensuring clear and immersive sound

Includes:

- 2 direct-replacement speakers & vehicle-specific speaker harness Specifications:
- 4" Woofer 1-Way Configuration
- Peak/RMS Power: 180W/60W
- · Sensitivity: 86dB
- Frequency Response: 100Hz 10kHz
- Impedance: 4 Ohm



OS-TESLA1T1" TWEETER SPEAKER KIT

Features:

- · Direct fit plugs and looms
- Precision-engineered silk dome tweeters
- Neodymium magnets deliver immense motor force while maintaining compact size and lightweight design

Includes:

• 2 direct-replacement speakers & vehicle-specific speaker harness

Specifications:

- 1" Tweeter 1-Way Configuration
- Peak/RMS Power: 120W/40W
- · Sensitivity: 92dB
- Frequency Response: 4.5KHZ-25kHz
- Impedance: 4 Ohm



OS-TESLACTR CENTER CHANNEL SPEAKER KIT

Features:

- Direct fit plugs
- Lightweight, rigid composite paper and wood fiber cone design for a natural vocal reproduction
- Precision-engineered silk dome tweeters
- Neodymium magnets deliver immense motor force while maintaining compact size and lightweight design

Includes:

• 2 direct-replacement speakers & vehicle-specific speaker harness

Specifications:

- 1" Tweeter & 4" Midrange 2-Way Configuration
- Peak/RMS Power: 180W/60W
- · Sensitivity: 86dB
- Frequency Response: 100HZ-22kHz
- Impedance: 4 Ohm



