

IR ACCESSORY CAMERA WITH MULTI-MOUNTS AND ACTIVE PARKING LINES



CELEBRATING
75
YEARS



TE-2MPIR

IR ACCESSORY CAMERA WITH MULTI-MOUNTS AND ACTIVE PARKING LINES



SALES 386-257-2956

PRODUCT OVERVIEW

See an unobstructed view while driving with a rear camera that can stay active while the vehicle is on, not just when it is in reverse*. This universal camera is ideal for keeping an eye on cargo, a trailer hitch, or reducing blind spots in the back of the vehicle while driving. iBEAM's TE-2MPIR camera features active parking lines that are shown the entire time the camera is on. For easy installation, a license plate mount and surface mount are included, along with a 27ft. extension harness. This camera has a resolution of 640 TV lines (CVBS) or 1280 TV lines (AHD), a 1/3" CMOS sensor, and a 150-degree viewing angle (CVBS) or 152-degree viewing angle (AHD). It features an improved power circuit, is rated IP67 for water resistance and has a durable metal housing.



* When used with a compatible monitor. Recommended for use with iBEAM's TE-43VS, TE-50VS and TE-7VS).

Features:

- Multiple mounts included - behind plate mount and surface mount
- Improved power circuit
- Can be viewed while driving, with compatible motor
- IP Rating: IP67
- Active parking lines
- 3 year warranty

Wire Lengths:

- Extension cable: 8.2M / 27'
- Camera cable: 1.5M / 5'

Specs:

Image sensor: 1/3" CMOS Image Sensor
TV System: CVBS: 640TV lines AHD: 1280TV lines
Effect Pixels 1280(H) x 720(V)
Pixel Size 3.75 μ mx 3.75 μ m
Min illumination 0.1 Lux
Video Out 1MP, 720P@60fps
Sensitivity 12448mV/Lux-s
Power Supply 9-16VDC
Lens Spec. 6G+IRF
Diagonal Viewing Angle: AHD 152°; CVBS 150°
Current Consumption \leq 120mA
Operating Temperature -20° to +70° C
Storage Temperature -30° to +85° C