

# TE-43VS User Manual

iBeamUSA.com MetraDealer.com techsupport@metra-autosound.com




## 1. Monitor



## 2. Main specifications and functions

- ODisplay: 4.3 inch(16:9)
- ©Power:≤3W
- ○Power supply:DC 12 V
- ©Pixel: 480 W \*RGB\*272 H)
- Contrast:350:1
- ○NTSC / PAL compatible
- OAV signal auto detect power on/off
- OAuto switch when reversing
- ©2 video inputs

## 3.Connection



1

Notes:			

### **IMPORTANT**

If you are having difficulties with the installation of this product, please call our Tech Support line at 1-800-253-TECH. Before doing so, look over the instructions a second time, and make sure the installation was performed exactly as the instructions are stated. Please have the vehicle apart and ready to perform troubleshooting steps before calling.



#### KNOWLEDGE IS POWER

Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry. Log onto www.installerinstitute.com or call 800-354-6782 for more information and take steps toward a better tomorrow.



Metra recommends MECP certified technicians

## Attention

When connecting with power cable, please make sure not to mistake the positive and negative pole, otherwise the fuse will blow immediately for security protection. If it happens, please replace the blown fuse with a new one with same specification, after connecting properly to the right pole. Don't randomly increase the current rating of the fuse, and NEVER use metal wire as a substitute.