

MULTI-MOUNT ACCESSORY CAMERA WITH ACTIVE PARKING LINES



CELEBRATING
75
YEARS



TE-2MPTC MULTI-MOUNT ACCESSORY CAMERA WITH ACTIVE PARKING LINES



SALES 386-257-2956

PRODUCT OVERVIEW

See an unobstructed view while driving with a rear camera that can stay active while the vehicle is on, not just when it is in reverse*. This universal camera is ideal for keeping an eye on cargo, a trailer hitch, or reducing blind spots in the back of the vehicle while driving. iBEAM's TE-2MPTC camera features active parking lines that are shown the entire time the camera is on. For easy installation, a license plate mount and surface mount are included, along with a 27ft extension harness. This camera has a resolution of 640 TV lines (CVBS) or 1280 TV lines (AHD), a 1/3" CMOS sensor, and a 150-degree viewing angle (CVBS) or 152-degree viewing angle (AHD). It features an improved power circuit, is rated IP67 for water resistance, and has a durable metal housing.

* When used with a compatible monitor. Recommended for use with iBEAM's TE-43VS, TE-50VS, and TE-7VS.



Wire Lengths:

- Extension cable: 8.2M / 27'
- Camera cable: 1.5M / 5'

Features:

- Multiple mounts included - behind plate mount and surface mount
- Improved power circuit
- Can be viewed while driving, with a compatible monitor
- IP rating: IP67
- Active parking lines
- 3-year warranty

Specs:

Image sensor: 1/3 inch CMOS
TV system CVBS: 640TV lines AHD: 1280TV lines
Effect pixels: 1280(H) x 720(V)
Pixel size: 3.75 Qmx 3.75 Qm
Min illumination: 0.1 lux
Video out: 1MP, 720P@60fps
Sensitivity: 12448mV/lux-s
Power supply: 9-16VDC
Lens spec: 6G+11RF
Diagonal viewing angle: AHD 152°; CVBS 150°
Current consumption: ≤ 120mAh
Operating temperature: -20 to +70°C
Storage temperature: -30 to +85° C

