



HE-MU47-SLM

Instructions

(thread-lock is recommended on all hardware, and silicone for all holes drilled)

- 1) Place the lightbar on the vehicle's roof. Adjust the foot rests in the slide track so that the lightbar sits level and stable.
- 2) Tighten down the foot rest screws to lock them in place.
- 3) Align the catch bars with the lightbar and over the rain guard. Identify the correct hole on the catch bar to connect the mounting plate.
- 4) Bolt the mounting plate to the catch bar using the included hardware.
- 5) Attach the catch bars to the lightbar using the included hardware. To not tighten down at this time.
- 6) Screw the catch bars into the rain guard. Make sure to check clearance before drilling/screwing.
- 7) Now, tighten down the bolt securing the catch bars to the lightbar. Work both sides evenly. When complete there should be no wiggle/movement of the lightbar, and the mounting plate should be flush against the lightbar bracket.



- 8) Find a suitable location for the controller. Clean thoroughly and dry.
- 9) Mount controller dock using the double sided tape.
- 10) Route the cable from the lightbar through the vehicle, avoiding any pinch points.
 - a) The main cable connects to the vehicle battery, red wire to +12VDC, black wire to chassis ground.
 - b) Connector cable runs to the controller.
- 11) Plug in controller and place in dock.

Controller dock holds controller magnetically

****Please periodically check that all hardware is tight and has not loosened over time.**