



#### INTERFACE COMPONENTS

- AXDSPX-CH5 interface
- AXDSPX-CH5 interface harness
- AXDSPX-CH5 vehicle T-harness
- Bass knob
- LD-DSP-RPAD2

#### APPLICATIONS

Visit [AxxessInterfaces.com](http://AxxessInterfaces.com) for current application list

For **Dash Disassembly Instructions**, refer to [metraonline.com](http://metraonline.com). Enter the year, make, and model of the vehicle in the **Vehicle Fit Guide** for **Radio Install kits**.



## DSP Data Interface with Pre-Wired Harness Fits Select Chrysler Models 2013-2023

#### INTERFACE FEATURES

- Designed for amplified and non-amplified systems
- Selectable 31-band Graphic EQ or 5-band parametric EQ on each channel with high pass, low pass, and bandpass filters
- 6 inputs and 10 individually assignable outputs
- Selectable slope (12, 24, 36, or 48db per octave)
- Selectable Graphic or Parametric EQ
- Independent equalization on each of the 10 outputs
- Each channel can be delayed independently up to 10 ms
- Clipping detection and limiting circuits
- Bass knob included
- Retains OE voice prompts (Uconnect®) if vehicle is equipped
- Retains factory chimes, including parking sensor and cross path detection alerts if vehicle is equipped
- Settings adjusted wirelessly in the free AX-DSP-XL app available for smartphones and tablets
- Easy behind the radio installation
- Can be used with factory and aftermarket radios
- Read, write, and store configurations for future recall
- Password protect feature available in the app
- Micro "B" USB updatable

#### TABLE OF CONTENTS

Installation & Installation Options .....	2
Connections .....	3-4
Rebooting the U-Connect Radio .....	5
Mobile App: Quick Setup .....	6-7
Specifications .....	8

#### TOOLS & INSTALLATION ACCESSORIES REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink
- Tape
- Wire cutter
- Zip ties
- Multimeter

#### Download AX-DSP-XL App

Android™ 9 or higher



iOS 12.1 or higher



**ATTENTION:** With the key out of the ignition, disconnect the negative battery terminal before installing this product. Ensure that all installation connections, especially the air bag indicator lights, are plugged in before reconnecting the battery or cycling the ignition to test this product.

**NOTE:** Refer also to the instructions included with the aftermarket accessory before installing this device.

## INSTALLATION OPTIONS

### **Adding a subwoofer to a factory system:**

This feature offers the ability to add a subwoofer to a factory system, whether amplified or non-amplified (Refer to [Page 3](#))

### **Adding a full-range amp and subwoofer to a factory system:**

This feature offers the ability to add a full-range amp and sub to a factory system, whether amplified\* or non-amplified. (Refer to [Page 4](#))

\* For amplified models the amp must be bypassed/unplugged, and **With OE Amplifier** chosen in the **Configuration** tab under Vehicle Type. Use either Axxess **AXABH-CH2** or **AXABH-CH4** (sold separately) to bypass the amp for best results.

**Note:** The interface provides a 12-volt 1-amp output to turn on aftermarket amp(s). If installing multiple amps, an SPDT automotive relay will be required if the amp turn-on current of all amps combined exceeds 1-amp. See [MetraOnline.com](#) for available relays.


## INSTALLATION

1. Disassemble the dash, unplug all connectors, and then remove the factory radio.\*
2. Install the **AXDSPX-CH5 vehicle T-harness** to the vehicle and make all necessary connections, but leave the amp turn-on wire disconnected.
3. Plug the **AXDSPX-CH5 vehicle T-harness** to the **AXDSPX-CH5 interface**.
4. Download and install the **AX-DSP-XL app** for your smart device.
5. Open the app then select the **Bluetooth® Connection** tab. Follow the instructions to pair the mobile device to the interface. Refer to [Page 6](#) for more information.
6. Scroll to the **Configuration** tab then select the vehicle type. Press the **Lock Down**\*\* button to save the configuration. Refer to [Page 7](#) for more information.
7. Connect the amp turn-on wire.
8. Adjust the settings in the app as desired. Press the **Lock Down** † button to save any new configurations.


\* For dash disassembly instructions, refer to [metraonline.com](#). Enter the year, make, and model of the vehicle in the Vehicle Fit Guide and find instructions under Metra Radio Install kits.

\*\* Anytime the interface is locked down the key must be cycled off then back on.

## ADDING A SUBWOOFER TO A FACTORY SYSTEM



## ADDING A FULL-RANGE AMP & SUB TO A FACTORY SYSTEM



## REBOOTING THE U-CONNECT RADIO



- The factory **U-Connect Radio** will require a reboot process to accept the aftermarket interface/or add a camera . Disconnecting the main harness to install a T-harness and repowering the radio may cause **U-Connect Radio** to program as a different model of vehicle than it was programmed to originally. Below are the different **U-Connect** initial **Splash/Boot Up** screens for vehicle types.

### SPLASH/BOOT UP COLORS

**Chrysler:** Blue

**Dodge/Ram:** Red

**Jeep:** Orange

### REBOOTING STEPS

1. Turn the Key or Press **Push to Start** Button to the ACC position.  
**DO NOT** press brake on **Push to Start** vehicles.
2. Press the Volume **PWR/MUTE** button and **TUNE/ENTER** button for 10-16 seconds, until the radio reboots.
3. Let go once the radio reboots, now you have successfully rebooted your factory radio.


## MOBILE APP: QUICK SETUP STEPS THROUGH AX-DSP-XL APP

**Download AX-DSP-XL App**  
Android® 9 or higher




1. Download and install the **AX-DSP-XL app** for your smart device.
2. Turn Vehicle Ignition on. Make sure the Remote Turn on lead is disconnected.
3. Open the app: Select **Bluetooth Connections** page.
  - Select **Scan**, all available AXDSP devices within range will be displayed. Select your AXDSP and hit connect. (Figure A)
4. Select the Configuration page.
  - Select **Vehicle Type** Icon
  - Select the Vehicle Make: \_\_\_\_\_ (Example: **DODGE**)
  - Select the Vehicle's model: \_\_\_\_\_ (Example: **DURANGO**)
  - Select **With OE Amp** or **Without OE Amp**
  - Hit **Apply** (Figure B)
5. Make sure radio volume is all the way down.
6. Connect the amp turn-on wire from the **AXDSPX-CH5 T-harness** to the aftermarket amplifiers.

iOS® 12.1 or higher




(Figure A)



(Figure B)

7. From the **Configuration** page click the **Identify** button to confirm that the **AXDSPX-CH5** is connected properly. If so, a chime will be heard from the front left speaker.
8. Press the **Lock Down** button to save the configuration. (Do not turn ignition off until this process is completed) (Figure C)
9. Select the **Bluetooth Configurations** page and disconnect the DSPX.
10. Turn ignition off, close all door then lock vehicle using the key fob. The vehicle will need to sit uninterrupted for 10 minutes while the vehicle goes to sleep. (Make sure Key fob is 15 feet away from the vehicle)
11. Unlock Vehicle, turn ignition on and test radio's functions.
12. Adjust the DSP settings in the app as desired. Refer to the instructions under the **Setup Instructions** tab, or online at [Axxessinterfaces.com](http://Axxessinterfaces.com) for an explanation of each tab in the app.

### Locking Down Data



(Figure C)

**Last and the most important:  
You MUST lock down your  
configuration and cycle the key!!!**

**SPECIFICATIONS**

Input Impedance	1M Ohm
Input Channels	6 High/Low level selectable
Input Options	High Level or Low Level selectable
Input Type	Differential-Balanced
Input Voltage	
High Level Range	0 - 28-volts Peak to Peak
Input Voltage	
Low Level Range	0 - 4.9-volts Peak to Peak
Output Channels	10
Output Voltage	Up to 5-volts RMS
Output Impedance	50 Ohms
Equalizer Type	31 Band Graphic EQ, +/-10dB
THD	<0.03%
Frequency Response	20Hz - 20kHz
Crossover	3-Way LPF, BPF, HPF THP per channel
Crossover Type	Linkwitz-Riley 24DB Slope, Fixed
Sampling	48kHz
S/N Ratio	105dB @ 5-volts RMS

**General**

Operating Voltage	10 - 16-volts DC
Standby Current Draw	-7mA
Operation Current Draw	-150mA
Adjustments/Controls	Application via Bluetooth
Remote Output	12-volts DC, Signal Sense or with Ignition

Having difficulties? We're here to help.



Contact our Tech Support line at:

**386-257-1187**Or via email at:  
[techsupport@metra-autosound.com](mailto:techsupport@metra-autosound.com)**Tech Support Hours (Eastern Standard Time)**

Monday - Friday: 9:00 AM - 7:00 PM

Saturday: 10:00 AM - 5:00 PM

Sunday: 10:00 AM - 4:00 PM

**Metra recommends MECP certified technicians**