



AXBUCH-MZ6V

INSTRUCCIONES DE INSTALACIÓN

Arnés Para Conservar o Agregar Cámara Compatible con Ciertos Modelos de Mazda 2007-2015

CARACTERÍSTICAS DE LA INTERFASE

- Retiene la cámara de reversa de fábrica para un radio de mercado secundario
- Permite que se añada una cámara de mercado secundario a la pantalla de fábrica
 - Incluye el AXCS-D-6V de 12 voltios al convertidor de 6 voltios

COMPONENTES DE LA INTERFASE

- Arnés AXBUCH-MZ6V • AXCS-D-6V 12 voltios al convertidor de 6 voltios

APLICACIONES

MAZDA

CX-5	2013-2015
CX-7	2007-2012
CX-9	2007-2015
MAZDA 6	2011-2015

HERRAMIENTAS REQUERIDAS

- Cortacables • Ponchadora • Pistola soldadora • Cinta
- Conectores (ejemplo: conectores de extremo, de campana, etc.)

¡PRECAUCIÓN! Todos los accesorios, interruptores, paneles de controles de clima y especialmente las luces del indicador de las bolsas de aire deben estar conectados antes de ciclar la ignición. Además, no quite el radio de fábrica con la llave en la posición o de encendido ni con el vehículo funcionando.

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V

INSTALLATION INSTRUCTIONS

Camera Retention/Add-on Harness Fits Select Mazda Models 2007-2015

INTERFACE FEATURES

- Retains the factory backup camera to an aftermarket radio
- Allows an aftermarket camera to be added to the factory screen
 - Includes the AXCS-D-6V 12-volt to 6-volt converter

INTERFACE COMPONENTS

- AXBUCH-MZ6V harness • AXCS-D-6V 12-volt to 6-volt converter

APPLICATIONS

MAZDA

CX-5	2013-2015
CX-7	2007-2012
CX-9	2007-2015
MAZDA 6	2011-2015

TOOLS REQUIRED

- Wire cutter • Crimping tool • Solder gun • Tape
- Connectors (example: butt connectors, bell caps, etc.)

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V

INSTRUCCIONES DE INSTALACIÓN

Arnés Para Conservar o Agregar Cámara Compatible con Ciertos Modelos de Mazda 2007-2015

CARACTERÍSTICAS DE LA INTERFASE

- Retiene la cámara de reversa de fábrica para un radio de mercado secundario
- Permite que se añada una cámara de mercado secundario a la pantalla de fábrica
 - Incluye el AXCS-D-6V de 12 voltios al convertidor de 6 voltios

COMPONENTES DE LA INTERFASE

- Arnés AXBUCH-MZ6V • AXCS-D-6V 12 voltios al convertidor de 6 voltios

APLICACIONES

MAZDA

CX-5	2013-2015
CX-7	2007-2012
CX-9	2007-2015
MAZDA 6	2011-2015

HERRAMIENTAS REQUERIDAS

- Cortacables • Ponchadora • Pistola soldadora • Cinta
- Conectores (ejemplo: conectores de extremo, de campana, etc.)

¡PRECAUCIÓN! Todos los accesorios, interruptores, paneles de controles de clima y especialmente las luces del indicador de las bolsas de aire deben estar conectados antes de ciclar la ignición. Además, no quite el radio de fábrica con la llave en la posición o de encendido ni con el vehículo funcionando.

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V

INSTALLATION INSTRUCTIONS

Camera Retention/Add-on Harness Fits Select Mazda Models 2007-2015

INTERFACE FEATURES

- Retains the factory backup camera to an aftermarket radio
- Allows an aftermarket camera to be added to the factory screen
 - Includes the AXCS-D-6V 12-volt to 6-volt converter

INTERFACE COMPONENTS

- AXBUCH-MZ6V harness • AXCS-D-6V 12-volt to 6-volt converter

APPLICATIONS

MAZDA

CX-5	2013-2015
CX-7	2007-2012
CX-9	2007-2015
MAZDA 6	2011-2015

TOOLS REQUIRED

- Wire cutter • Crimping tool • Solder gun • Tape
- Connectors (example: butt connectors, bell caps, etc.)

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V
INSTALLATION INSTRUCTIONS

Connections to be made

The AXBUCH-MZ6V can be connected two different ways

To retain the factory backup camera to an aftermarket radio:

- Connect the **Black** wire to chassis ground, and also to the **Black** wire of the AXCS-D-6V.
- Connect the **Yellow** wire to the **Blue/Red** wire of the AXCS-D-6V.
- Connect the reverse wire from the aftermarket radio, to the reverse signal in the vehicle, and also to the **Blue/White** wire of the AXCS-D-6V.
- Connect the **male Yellow** RCA jack to the rear camera input of the aftermarket radio.

To allow an aftermarket camera to be added to the OEM screen:

- Connect the **female Yellow** RCA jack to the aftermarket camera.
- The AXCS-D-6V 12-volt to 6-volt converter will not be used in this application.
- Tape off and disregard the following (2) wires, they will not be used in this application; **Black, Yellow**

IMPORTANT

If you are having difficulties with the installation of this product, please call our Tech Support line at **386-257-1187**. Before doing so, look over the instructions a second time, and make sure the installation was performed exactly as the instructions are stated. Please have the vehicle apart and ready to perform troubleshooting steps before calling.



Metra recommends MECP
certified technicians

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V
INSTRUCCIONES DE INSTALACIÓN

Conexiones que se deben hacer

El AXBUCH-MZ6V puede conectarse de dos maneras distintas

Para retener la cámara de reversa de fábrica para un radio de mercado secundario:

- Conecte el cable **negro** a la tierra del chasis, y también para el cable **negro** del AXCS-D-6V.
- Conecte el cable **amarillo** al cable **azul/rojo** del AXCS-D-6V.
- Conecte el cable de marcha atrás del radio de mercado secundario, a la señal de marcha atrás en el vehículo, y también para el cable **azul/blanco** de la AXCS-D-6V.
- Conecte el conector RCA **macho amarillo** RCA en la entrada de la cámara de reversa del radio de mercado secundario.

Para agregar una cámara secundaria a la pantalla original:

- Conecte el conector RCA **hembra amarillo** a la cámara de mercado secundario.
- El AXCS-D-6V 12 voltios al convertidor de 6 voltios no se utilizará en esta solicitud.
- Aísle y omita los siguientes dos cables, no se usarán en esta aplicación: **Negro, Amarillo**

IMPORTANTE

Si tiene dificultades con la instalación de este producto, llame a nuestra línea de soporte técnico al **386-257-1187**. Antes de hacerlo, revise las instrucciones por segunda vez y asegúrese de que la instalación se haya realizado exactamente como se indica en las instrucciones. Por favor tenga el vehículo desarmado y listo para ejecutar los pasos de resolución de problemas antes de llamar.



Metra recomienda técnicos
certificados por MECP

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V
INSTALLATION INSTRUCTIONS

Connections to be made

The AXBUCH-MZ6V can be connected two different ways

To retain the factory backup camera to an aftermarket radio:

- Connect the **Black** wire to chassis ground, and also to the **Black** wire of the AXCS-D-6V.
- Connect the **Yellow** wire to the **Blue/Red** wire of the AXCS-D-6V.
- Connect the reverse wire from the aftermarket radio, to the reverse signal in the vehicle, and also to the **Blue/White** wire of the AXCS-D-6V.
- Connect the **male Yellow** RCA jack to the rear camera input of the aftermarket radio.

To allow an aftermarket camera to be added to the OEM screen:

- Connect the **female Yellow** RCA jack to the aftermarket camera.
- The AXCS-D-6V 12-volt to 6-volt converter will not be used in this application.
- Tape off and disregard the following (2) wires, they will not be used in this application; **Black, Yellow**

IMPORTANT

If you are having difficulties with the installation of this product, please call our Tech Support line at **386-257-1187**. Before doing so, look over the instructions a second time, and make sure the installation was performed exactly as the instructions are stated. Please have the vehicle apart and ready to perform troubleshooting steps before calling.



Metra recommends MECP
certified technicians

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25



AXBUCH-MZ6V
INSTRUCCIONES DE INSTALACIÓN

Conexiones que se deben hacer

El AXBUCH-MZ6V puede conectarse de dos maneras distintas

Para retener la cámara de reversa de fábrica para un radio de mercado secundario:

- Conecte el cable **Negro** a la tierra del chasis, y también para el cable **Negro** del AXCS-D-6V.
- Conecte el cable **Amarillo** al cable **Azul/Rojo** del AXCS-D-6V.
- Conecte el cable de marcha atrás del radio de mercado secundario, a la señal de marcha atrás en el vehículo, y también para el cable **Azul/Blanco** de la AXCS-D-6V.
- Conecte el conector RCA **macho Amarillo** RCA en la entrada de la cámara de reversa del radio de mercado secundario.

Para agregar una cámara secundaria a la pantalla original:

- Conecta el conector RCA **amarillo hembra** a la cámara del mercado secundario.
- El convertidor de 12 V a 6 V AXCS-D-6V no se usará en esta aplicación.
- Aísle y omita los siguientes dos cables, no se usarán en esta aplicación: **Negro, Amarillo**

IMPORTANTE

Si tiene dificultades con la instalación de este producto, llame a nuestra línea de soporte técnico al **386-257-1187**. Antes de hacerlo, revise las instrucciones por segunda vez y asegúrese de que la instalación se haya realizado exactamente como se indica en las instrucciones. Por favor tenga el vehículo desarmado y listo para ejecutar los pasos de resolución de problemas antes de llamar.



Metra recomienda técnicos
certificados por MECP

AXXESS Integrate • AxxessInterfaces.com

© COPYRIGHT 2025 METRA ELECTRONICS CORPORATION REV. 6/18/25